(51) International Patent Classification 7:

C07D 295/00

2

(21) International Application Number:

PCT/US99/22590

(22) International Filing Date: 28 September 1999 (28.09.99)

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT) (11) International Publication Number:

(43) International Publication Date: 6 April 2000 (06.04.00)

WO 00/18750

(30) Priority Data: 60/102,153 60/111,950 60/121,302 60/132,630 The present invention is directed to new, energy-efficient, photoinitistors having general formula (I) wherein X<sub>1</sub> is a conjugated system such as one or more myl group or substituted myl groups; Z<sub>1</sub> is -0, -3, an slyf group having from one to six cerbon atoms, an exter motily, a tenden motiley, an arise motiley, an either motiley, and are not entired and group, such as a size-containing group or a borro-containing group, respectively, and M<sub>1</sub> is an altip group, a substituted altiply group, or forms a five member ring with Z<sub>1</sub>. The present invention is also directed to a method of generating a restrive species, which includes exposing one or more photoinitistant to redistion to form one or more treative species. Also described are methods of configurating polymerizable protections, methods of curing an unsaturated oligomerimonomer mature, and methods of laminating using the photoinitistant of the present invention. In addition, the present invention is directed to inx compositions and resins, and methods of printing using the above-described photoinitistors. (71) Applicants: KIMBERLY-CILARK WORLDWIDE, INC. [USUIS]; 401 North Lake Street, Necath, WI 54956 (US), NOHR, Ronald, Sinclair (-US); 8955 Netbit Lakes Drive, Alphanetta, GA 50232 (US), MACDONALD, ichn., Gavin [-US]; 1472 Knollwood Terrace, Decatur, GA 30033 (US). (74) Agents: WITHERS, James, D.; Jones & Askew, LLP, 2400 Monarch Tower, 3424 Peachine Road, N.E., Atlanta, GA 30326 (US) et al. (57) Abstract (54) Tide: NOVEL PHOTOINITIATORS AND APPLICATIONS THEREFOR 28 September 1998 (28.09.98) 11 December 1998 (11.12.98) 23 February 1999 (23.02.99) 5 May 1999 (05.05.99) នននន (81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, MM, EE, BR, BY, CA, CH, CN, CR, CU, CZ, DE, MM, EE, BR, BY, CA, CH, CN, CR, CU, CZ, LE, LI, N, M, EE, BY, CR, CR, CR, CR, CR, CR, LI, TI, LU, LY, MD, MG, MK, MA, MW, MX, NO, AZ, PL, FT, RO, RU, SD, MG, MK, MA, MW, MX, NO, AZ, PL, FT, RO, RU, SD, SE, SG, SI, SK, SL, TI, TM, TE, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, AEDO pazars (DH, GM, AZ, BY, US, SD, SL, SZ, TZ, UG, ZW), Burstinn paters (AM, AZ, BY, US, CZ, ZMD, RU, TT, TM), European paters (AT, BE, CH, US, CY, DE, DM, ES, FI, FR, GB, GR, HE, TI, LU, MC, ML, FT, SEB, OAP) paters (GP, BH, CP, CO, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TO). Published
Withous international search report and to be republished upon receipt of that report. 3

## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pumphlets publishing international applications under the PCT.

			Liberta	E	Estonia	
		SE Sweden	Sri Lenka	Ę	Denmark	ÜK
			Liechsenstein	E	Germany	DE
			Saint Lucia	ភ	Czech Republic	ប
			Kerakstan	F	Othe	5
			Republic of Korea	K	Off	2
			Republic of Karea		Cameroon	ğ
			Democratic People's	ζ	Côte d'Ivoirs	Ω
Zimbabwe	¥3		Кутругана	Ģ	Switzerland	3
Yugoshwia	7		Kenya	K	Congo	8
Vict Nam	ž		Japan	¥	Central African Republic	Q
Unbekistan	S		Raly	7	Canada	ç
United States of America	æ		keland	ᅜ	Belgrus	ВY
Ugunda	ઠ		braci	F	Brazil	g
Utraine	Ķ		trained	Z	Benin	2
Trinidad and Tobago	7	_	Hungary	Ξ	Bulgaria	80
Turkey	겉		Oreace	유	Burkins Paso	Ę
Turkmenistas	¥		Cuines	2	Belgham	
Tajikistan	đ	_	Charns	윤	Berbados	8
Togo	ಕ	_	Georgia	CE	Bosnia and Herzegovina	5
R	귱	_	United Kingdom	8	Azerbaijan	À
Sweetland	ĸ	_	Cabon	ç	Australia	ځ
Senegal	Š	_	Rusco	78	Austria	4
Slovakia	SK	_	Pinland	3	Armenia	È
Slovenia	2		Spain	E	Albania	2

## NOVEL PHOTOINITIATORS AND APPLICATIONS THEREFOR

10

G

## Technical Field

15

The present invention relates to novel photoinitiators and methods for generating a reactive species using the photoinitiators. The present invention further relates to methods of polymerizing or photocuring polymerizable material using the above-mentioned photoinitiators. The photoinitiators of the present invention find particular utility in photocurable inks as used in ink jet printers or on a printing press with and without nitrogen blanketing.

## Background of the Invention

20

25

Polymers have served essential needs in society. For many years, these needs were filled by natural polymers. More recently, synthetic polymers have played an increasingly greater role, particularly since the beginning of the 20th century. Especially useful polymers are those prepared by an addition polymerization mechanism, i.e., free radical chain polymerization of unsaturated monomers, and include, by way of example only, coatings and adhesives. In fact, the majority of commercially significant processes are based on free-radical chemistry. That is, chain polymerization is initiated by a reactive species, which often is a free radical. The source of the free radicals is termed an initiator or photoinitiator.

ၶ

35

WO 00/18750

PCT/US99/22590

2

Improvements in free radical chain polymerization have focused both on (1) more reactive monomer and prepolymer materials and (2) the photoinitiator. Whether a particular unsaturated monomer can be converted to a polymer requires structural, thermodynamic, and kinetic feasibility. Even when all three exist, kinetic feasibility is achieved in many cases only with a specific type of photoinitiator. Moreover, the photoinitiator can have a significant effect on reaction rate which, in turn, may determine the commercial success or failure of a particular polymerization process or product.

5

A free radical-generating photoinitiator may generate free radicals in several different ways. For example, the thermal, homolytic dissociation of an initiator typically directly yields two free radicals per initiator molecule. A photoinitiator, i.e., an initiator which absorbs light energy, may produce free radicals by one of three pathways:

15

10

 the photoinitiator undergoes excitation by energy absorption with subsequent decomposition into one or more radicals;

20

- (2) the photoinitiator undergoes excitation and the excited species interacts with a second compound (by either energy transfer or a redox reaction) to form free radicals from the latter and/or former compound(s); or
- (3) the photoinitiator undergoes an electron transfer to produce a radical cation and a radical anion.

23

While any free radical chain polymerization process should avoid the presence of species which may prematurely terminate the polymerization reaction, prior photoinitiators present special problems. For example, absorption of the light by the reaction medium may limit the amount of energy available for absorption by the photoinitiator. Also, the often competitive and complex kinetics involved may have an adverse effect on the reaction rate. Moreover, some commercially available radiation sources, such as medium

ၶ

ယ

and high pressure mercury and xenon lamps, may emit over a wide wavelength range, thus producing individual emission bands of relatively low intensity. Many photoinitiators only absorb over a small portion of the emission spectra and, as a consequence, much of the lamps' radiation remains unused. In addition, most known photoinitiators have only moderate "quantum yields" (generally less than 0.4) at these wavelengths, indicating that the conversion of light radiation to radical formation can be more efficient.

S

dry/cure time only accomplished by multiple passes, as many photoinitiator and a high energy light source, the systems require a high energy radiation source to induce relatively large amount of photoinitiator in the ink printing." commercially available photoinitiator systems require a nitrogen blanket. Fourth, even with a large amount of are highly reactive to oxygen and must be used under a Third, many commercially available photoinitiator systems radiation source, often the cure results are unsatisfactory photocuring. Second, most of the commercially available photoinitiator leads to undesirable extractables within the ink composition. composition to fully cure/dry the ink composition. This commercially available photoinitiator systems require a have a number of shortcomings. printing. Commercially available photoinitiator systems on a Heidelberg press, flexographic printing, and flat-bed includes, for example, off-set printing operations, such as radiation as a drying means. Radiation-drying printing printing" refers to any printing method which utilizes compositions to accelerate ink drying in "radiation-drying including IRGACURE® 369, are presently used in ink As used herein, the term "radiation-drying commercially Moreover, even with the high energy available photoinitiators First, most of the

25

20

15

10

အ

WO 00/18750 PCT/US99/22590

as 15 passes, under a light source, which significantly limits the output of a radiation-drying printing press.

What is needed in the art is a new class of energy-efficient photoinitiators having unsurpassed photoreactivity even when exposed to a low energy light source, such as a 50 W excimer cold lamp. What is also needed in the art is a new class of energy-efficient photoinitiators that may be cured in air, as well as, a nitrogen atmosphere. Further, what is needed in the art is a class of photoinitiators having unsurpassed photoreactivity, for use in the radiation-drying printing industry, which will significantly increase the output of a radiation-drying printing press due to reduction in ink drying/curing time.

10

G

## Summary of the Invention

15

The present invention addresses some of the difficulties and problems discussed above by the discovery of energy-efficient photoinitiators having the following general formula:



20

wherein X<sub>1</sub> is a conjugated system such as one or more aryl groups or substituted aryl groups; Z<sub>1</sub> is -O<sub>1</sub> -S<sub>2</sub>, an alkyl group having from one to six carbon atoms, an ester moiety, a ketone moiety, an amine moiety, an imine moiety, an ether moiety, an aryl or substituted aryl group, a metal or nonmetal, or a metal or non-metal containing group, such as a zinc-containing group or a boron-containing group, respectively; and M<sub>1</sub> is an alkyl group, a substituted alkyl group, or forms a five-member ring with Z<sub>1</sub>. By selecting particular "X<sub>1</sub>", "Z<sub>1</sub>", and "M<sub>1</sub>" groups, photoinitiators are produced having a desired absorption maximum, which

25

PCT/US99/22590

5

substantially corresponds to an emission band of a radiation source and selectively varies from less than about 222 nm to greater than about 445 nm.

species in air or in a nitrogen atmosphere. Unlike many invention also efficiently generate one or more reactive excimer lamps and mercury lamps, as compared to prior art reactive species under extremely low energy lamps, such as invention is that they efficiently generate one or more times faster than the best prior art photoinitiators. photoinitiators of the present invention are as much as ten invention are not sensitive to oxygen. prior photoinitiators, the photoinitiators of the present photoinitiators. main advantages of the photoinitiators of the present irradiating the one or more photoinitiators. includes providing one or more of the photoinitiators and same, and methods for generating a reactive species which The present invention is directed to the abovephotoinitiators, compositions containing the The photoinitiators of the present Further, the One of the

10

5

The present invention is further directed to a method of efficiently generating a reactive species by matching a photoinitiator having an absorption maximum to an emission band of a radiation source, which corresponds to the absorption maximum. By adjusting the substituents of the photoinitiator, one can shift the absorption maximum of the photoinitiator from less than about 222 nm to greater than 445 nm.

23

20

15

The present invention is also directed to methods of using the above-described photoinitiators to polymerize and/or photocure a polymerizable material. The photoinitiators of the present invention result in rapid curing times in comparison to the curing times of prior art photoinitiators, even with relatively low output lamps. The present invention includes a method of polymerizing an polymerizable material by exposing the polymerizable

30

35

WO 00/18750

PCT/US99/22590

6

material to radiation in the presence of the efficacious wavelength specific photoinitiator composition described above. When an unsaturated oligomer/monomer mixture is employed, curing is accomplished.

G

The present invention further includes a film and a method for producing a film, by drawing an admixture of polymerizable material and one or more photoinitiators of the present invention, into a film and irradiating the film with an amount of radiation sufficient to polymerize the composition. The admixture may be drawn into a film on a nonwoven web or on a fiber, thereby providing a polymer-coated nonwoven web or fiber, and a method for producing the same.

10

The present invention is also directed to an adhesive composition comprising a polymerizable material admixed with one or more photoinitiators of the present invention. Similarly, the present invention includes a laminated structure comprising at least two layers bonded together with the above-described adhesive composition, in which at least one layer is a nonwoven web or film. Accordingly, the present invention provides a method of laminating a structure wherein a structure having at least two layers with the above-described adhesive composition between the layers is irradiated to polymerize the adhesive composition.

20

15

The present invention is further directed to a method of printing, wherein the method comprises incorporating one or more photoinitiators of the present invention into an ink composition; printing the ink onto a substrate; and drying the ink with a source of radiation.

25

These and other features and advantages of the present invention will become apparent after a review of the following detailed description of the disclosed embodiments and the appended claims.

ၶ

# Detailed Description of the Invention

The present invention is directed to energy-efficient, reactive, photoinitiators and methods for utilizing the same. More particularly, the present invention is directed to new photoinitiators having the following general formula:

G

wherein X<sub>1</sub> comprises a conjugated system such as one or more aryl groups or substituted aryl groups; Z<sub>1</sub> is -O, -S, an alkyl group having from one to six carbon atoms, an ester moiety, a ketone moiety, an amine moiety, an imine moiety, an ether moiety, an aryl or substituted aryl group, a metal or non-metal, or a metal or non-metal containing group, such as a zinc-containing group or a boron-containing group, respectively; and M<sub>1</sub> comprises an alkyl group, a substituted alkyl group, or forms a five-member ring with Z<sub>1</sub>.

15

10

The present invention is further directed to a method of efficiently generating a reactive species by matching a photoinitiator having an absorption maximum to an emission band of a radiation source, which corresponds to the absorption maximum. By adjusting the substituents of the photoinitiator, one can shift the absorption maximum of the photoinitiator from less than about 222 nm to greater than 445 nm.

8

The present invention also includes a method of polymerizing a polymerizable material by exposing the polymerizable material to electromagnetic radiation in the presence of one or more of the photoinitiators described above. Further, the present invention is directed to a film and a method for producing a film, by drawing an admixture of polymerizable material and one or more of the

8

25

WO 00/18750 PCT/US99/12590

œ

photoinitiators described above, into a film and irradiating the film with an amount of electromagnetic radiation sufficient to polymerize the admixture.

The present invention is further directed to an adhesive composition comprising a polymerizable material admixed and one or more photoinitiators of the present invention. Similarly, the present invention includes a laminated structure comprising at least two layers bonded together with the above-described adhesive composition. The present invention further provides a method of laminating a structure wherein a structure having at least two layers with the above-described adhesive composition between the layers is irradiated with appropriate electromagnetic radiation to polymerize the adhesive composition.

10

S

Definitions

15

20

cations. Cations also include those formed from various cations, such as triphenyl cation; cyclopropylmethyl cations, cation, t-hexyl cation; allylic cations; benzylic cations; aryl cation, ethyl cation, propyl cation, t-butyl cation, t-pentyl secondary, and tertiary alkyl carbocations, such as methyl alkylcarbonyl-carbenes, siloxycarbenes, and dicarbenes. carbenes. Illustrated below are examples of several of such not limited to, free-radicals, cations, anions, nitrenes, and include, by way of illustration, a proton; primary, (sometimes referred to as carbocations or carbonium ions) nitrene, alkyl nitrenes, and aryl nitrenes. Examples of nitrenes include, also by way of example, methylene or carbene, dichlorocarbene, diphenylcarbene, herein to mean any chemically reactive species including, but methoxymethyl cation; triarylsulphonium cations; and acyl As used herein, the term "reactive species" is used Examples of such carbenes include, for example, as tetra-n-butylammonium Cations

25

8

PCT/US99/22590

9

generally produce free radicals or cations. manganese fluorinated diaryltitanocenes, organometallic photoinitiators include titanocenes, phosphorus-containing alkyl anions. Finally, examples of anions; benzylic anions; aryl cations; and sulfur- or anion, cyclobutyl anion, and cyclopentyl anion; allylic and neopentyl anion; cycloalkyl anions, such as cyclopropyl anions, such as ethyl anion, n-propyl anion, isobutyl anion, referred to as carbanions) include, by way of example, alkyl thallium(I) triflates. Examples of anions (sometimes vanadium tetrachloride; and silver, copper(I) and (II), and manganese tricarbonyl. tetrahaloaurate(III) salts; sodium tetrachloroaurate(III) decacarbonyl, and methylcyclopentadienyl Organometallic photoinitiators iron arene complexes,

As used herein, the term "quantum yield" is used herein to indicate the efficiency of a photochemical process. More particularly quantum yield is a measure of the probability that a particular molecule will absorb a quantum of light during its interaction with a photon. The term expresses the number of photochemical events per photon absorbed. Thus, quantum yields may vary from zero (no absorption) to 1.

20

15

10

G

As used herein, the term "polymerization" is used herein to mean the combining, e.g. covalent bonding, of a number of smaller molecules, such as monomers, to form large molecules, i.e., macromolecules or polymers. The monomers may be combined to form only linear macromolecules or they may be combined to form three-dimensional macromolecules, commonly referred to as crosslinked polymers.

23

As used herein, the term "curing" means the polymerization of functional oligomers and monomers, or even polymers, into a crosslinked polymer network. Thus, curing is the polymerization of unsaturated monomers or oligomers in the presence of crosslinking agents.

35

ဗ

WO 00/18750

PCT/US99/22590

10

As used herein, the terms "unsaturated monomer," "functional oligomer," and "crosslinking agent" are used herein with their usual meanings and are well understood by those having ordinary skill in the art. The singular form of each is intended to include both the singular and the plural, i.e., one or more of each respective material.

G

As used herein, the term "unsaturated polymerizable material" is meant to include any unsaturated material capable of undergoing polymerization. The term encompasses unsaturated monomers, oligomers, and crosslinking agents. Again, the singular form of the term is intended to include both the singular and the plural.

10

As used herein, the term "fiber" as used herein denotes a threadlike structure. The fibers used in the present invention may be any fibers known in the art. As used herein, the term "nonwoven web" as used herein denotes a web-like matter comprised of one or more overlapping or interconnected fibers in a nonwoven manner. It is to be understood that any nonwoven fibers known in the art may be used in the present invention.

15

Photoinitiators

2

The present invention is directed to new photoinitiators having the following general formula:

25

$$x_1 = C$$
 $X_1 = C$ 
 $X_1 = C$ 

wherein  $X_1$  is a conjugated system such as one or more aryl groups or substituted aryl groups;  $Z_1$  is -O, -S, an alkyl group having from one to six carbon atoms, an ester moiety, a ketone moiety, an amine moiety, an imine moiety, an ether moiety, an aryl or substituted aryl group, a metal or nonmetal, or a metal or non-metal containing group, such as a

မ

=

zinc-containing group or a boron-containing group, respectively; and  $M_1$  is an alkyl group, a substituted alkyl embodiment of the present invention,  $X_1$  comprises group, or forms a five-member ring with Z<sub>1</sub>. In one

G

ç

wherein  $R_{\phi}$  and  $R_{7}$  each independently represent hydrogen, an alkyl group having from one to six carbon atoms, an from one to six carbon atoms, an aryl group, independently represent a hydrogen, an alkyl group having halogen-substituted alkyl group; and wherein  $y_1$  and  $y_2$  each alkoxy group having from one to six carbon atoms, or a

15

10

WO 00/18750

PCT/US99/22590

12

wherein  $X_3$  represents a hydrogen, an alkyl or substituted alkyl group, or an aryl or substituted aryl group. Other suitable  $X_1$  groups include, but are not limited to, the following:

G

ç

5

group, an ethyl group, an isopropyl group, a methoxy group, an ethoxy group, or a trifluoromethyl group. In a further embodiment of the present invention,  $M_1$ Desirably, R6 and R7 each independently represent a methyl

15

comprises a tertiary alkyl group having the following formula:

13

wherein  $y_3$ ,  $y_4$  and  $y_5$  each independently represent a hydrogen, an alkyl group having from one to six carbon atoms, a tertiary amine group, an aryl group, or a substituted aryl group.

G

In one embodiment of the present invention, the photoinitiator has the following structure:

5

In the above structure, a calcium ion forms a five member ring, which includes the oxygen atom (" $Z_1$ ") and the electron-rich nitrogen atom. As used herein, an arrow represents a coordinate covalent bond between an electron-rich nitrogen atom and a metal or non-metal cation. It should be understood that other cations may be used instead of the calcium ion. Other suitable cations include, but are not limited to, beryllium, magnesium, strontium, barium, zinc, aluminum, and copper (II).

15

In a further embodiment, Z<sub>1</sub> in the above-described general formula comprises an ester moiety. Examples of such photoinitiators include, but are not limited to, photoinitiators having the following structure:

20

WO 00/18750

PCT/US99/22590

14

In the above photoinitiators, it should be noted that the -C(O)CH<sub>3</sub> group ("Z<sub>1</sub>") may be substituted with other groups including, but not limited to, -CH<sub>3</sub> -BF<sub>3</sub> and phenyl groups.

G

In yet a further embodiment, the photoinitiators of the present invention have the following general formula:

10

wherein  $X_i$  is as defined above;  $Z_2$  is a metal or non-metal cation, such as  $Zn^2$ ,  $Ca^2$ , or boron, or a salt thereof, or -C(O)R, which forms a covalent bond with the oxygen

15

hydrogen atom, an alkyl or substituted alkyl group, or an aryl or substituted aryl group. In a further embodiment,  $R_1$ atom; and R, R1, R2, R3, and R4 are each independently a

and  $R_2$  may form one or more aromatic rings with  $X_1$ .

Photoinitiators having the above formula include, but are not limited to, the following photoinitiators:

បា

and

general formula, is shown below: One photoinitiator of particular interest, having the above

10

$$\begin{array}{c} R_{13} - N \\ R_{12} - N \\ R_{12} - R_{11} \end{array}$$

WO 00/18750

PCT/US99/22590

PCT/US99/22590

16

wherein  $R_{11}$ ,  $R_{12}$ ,  $R_{13}$ , and  $R_{14}$  are each independently a hydrogen atom; an alkyl group or substituted alkyl group. In one embodiment of the present invention, the

photoinitiator has the following structure:

G

photoinitiator has the following structure: In a further embodiment of the present invention, the

15

10

20

aluminum, scandium, and copper (II). For example, another photoinitiator of the present invention may have the Other suitable salts include, but are not limited to, salts electron-rich nitrogen atom. It should be understood that member ring, which includes the oxygen atom and the following structure: containing beryllium, magnesium, strontium, barium, zinc, other salts may be used instead of the calcium chloride. In the above structure, the calcium atom forms a five

structure below: or more aromatic rings to form a photoinitiator having the  $R_{2}$ , and  $X_{1}$  of the above-described general formula form one In a further embodiment of the present invention,  $R_1$ ,

G

and y<sub>11</sub> and y<sub>12</sub> are each independently represent a hydrogen; an alkyl group having from one to six carbon atoms; an aryl group; wherein  $Z_{\nu}$ ,  $R_{3\nu}$  and  $R_{4\nu}$  are substituents as defined above

5

WO 00/18750

PCT/US99/22590

18

wherein  $X_3$  is defined above.

S

photoinitiators having the following general formula: The present invention is further directed to novel

$$x_1 = C$$

$$R$$

$$R$$

$$R$$

$$R$$

$$R$$

$$R$$

$$R$$

group, an ethyl group, a propyl group, or a benzyl group.
In one embodiment of the present invention, the nonmetals and nonmetal salts containing boron and phosphorus. Desirably, Z<sub>3</sub> comprises a chloride-containing cation or a salt containing the cation; and  $X_1$ ,  $R_1$ ,  $R_2$ ,  $R_3$ ,  $R_4$ , and  $R_5$  are as defined above. Suitable  $Z_5$  groups include, but chloride. Desirably, "R" comprises hydrogen, a methyl salt such as zinc chloride, zinc benzyl chloride, or boron are not limited to, metals and metal salts containing Cd, Hg, wherein Y is -O- or -N( $R_5$ )-;  $Z_3$  is a metal or nonmetal Zn, Al, Ga, In, Tl, Sc, Ge, Pb, Si, Ti, Sn, and Zr, as well as,

15

5

photoinitiator has the following structure:

$$\begin{pmatrix} & & & & & & \\ & & & & & \\ & & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & \\ & & & \\ &$$

19

wherein  $X_4$  comprises any nitrogen-containing group, which donates a pair of electrons to the nitrogen-carbon double bond; and  $R_1$ ,  $R_2$ ,  $R_3$ ,  $R_4$ ,  $R_6$ , and  $R_7$  are as defined above. The above photoinitiator has an absorption maximum of about 360 nm. In a further embodiment of the present invention, the photoinitiator has the following structure:

S

wherein  $X_4$ ,  $R_1$ ,  $R_2$ ,  $R_3$ ,  $R_4$ ,  $R_6$ , and  $R_7$  are as defined above. By replacing the zinc chloride with boron chloride, the absorption maximum of the photoinitiator shifts to about 410 nm.

10

10

Other photoinitiators of the present invention have the following structure:

wherein X<sub>4</sub>, R<sub>1</sub>, R<sub>2</sub>, R<sub>3</sub>, R<sub>4</sub>, R<sub>5</sub>, R<sub>6</sub>, and R<sub>7</sub> are as defined above. In one embodiment of the present invention, the photoinitiator has the following structure:

15

20

WO 00/18750

20

PCT/US99/22590

$$X_{0}$$
 $X_{0}$ 
 $X_{0$ 

wherein X<sub>4</sub>, R<sub>1</sub>, R<sub>2</sub>, R<sub>3</sub>, R<sub>4</sub>, R<sub>5</sub>, R<sub>6</sub>, and R<sub>7</sub> are as defined above. By replacing the oxygen atom with a nitrogen atom in the five member ring, the absorption maximum of the photoinitiator shifts further to greater than about 410 nm. It should be noted that other metal and nonmetal salts may be used in place of the metal and nonmetal chlorides. For example, the above photoinitiator may have the following structure:

S

$$R_1$$
 $R_2$ 
 $R_3$ 
 $R_3$ 
 $R_3$ 
 $R_3$ 
 $R_3$ 

The above-described photoinitiators of the present invention may be produced by the following reaction mechanism:

15

$$\frac{\text{vectoring}}{\text{couping}} > X - C \qquad X - R_4 + Z_3 \longrightarrow X = C \qquad X - R_4$$

$$\frac{N}{R_1} - R_3 \qquad X = C \qquad X - R_4$$

$$\frac{N}{R_2} - R_3 \qquad R_3 \qquad R_3$$

wherein a first compound reacts with a metal or metal salt or a nonmetal or nonmetal salt,  $Z_y$ , to produce a

21

photoinitiator of the present invention, having a fivemember ring containing a metal or nonmetal atom, at least one nitrogen atom, two carbon atoms, and possibly an oxygen atom.

In a further embodiment of the present invention, the photoinitiators have the following general formula:

S

$$x_1 = C$$

$$x_2 = C$$

$$x_1 = C$$

$$x_2 = C$$

$$x_2 = C$$

$$x_3 = C$$

$$x_4 = C$$

each independently comprise BF4, AsF6, PF6, or SbF6. comprise fluorine, chlorine or bromine-containing anions. containing anions. Desirably, Z, and Z, each independently and Z<sub>6</sub> groups include, but are not limited to, halogennitrogen atom donates its lone electron pair to metal or nonmetal atom,  $Z_4$ , to form a five member ring. Suitable ,  $Z_4$ without R3 or R4. In the above photoinitiator structure, the containing anions or form one or more rings with or is a metal or nonmetal atom; and Z<sub>5</sub> and Z<sub>6</sub> are halogenor a benzyl group. hydrogen, a methyl group, an ethyl group, a propyl group Desirably, R<sub>1</sub>, R<sub>2</sub>, R<sub>3</sub>, and R<sub>4</sub> each independently comprise fluorine-containing anions. Even more desirably, Z, and Z, More desirably,  $Z_5$  and  $Z_6$  each independently comprise phosphorus. More desirably, Z4 comprises Zn. Suitable Z5 Desirably, Z<sub>4</sub> comprises Cd, well as, nonmetals such as boron and phosphorus. Hg, Zn, Mg, Al, Ga, In, Tl, Sc, Ge, Pb, Si, Ti, Sn and Zr, as groups include, but are not limited to, metals such as Cd, wherein  $X_1$ , Y,  $R_1$ ,  $R_2$ ,  $R_3$ ,  $R_4$ , and  $R_5$  are as defined above;  $Z_4$ Zn, Mg, Ti, boron or

20

15

5

23

WO 00/18750 PCT/US99/22590

23

In one embodiment of the present invention, the photoinitiator has the following structure:

$$\begin{array}{c} x_1 = C \\ x_2 = C \\ x_3 = C \\ x_4 = C \\ x_5 = C \\ x_7 = C \\ x_8 = C \\$$

wherein  $X_1$ , Y,  $R_1$ ,  $R_2$ ,  $R_3$ ,  $R_4$ ,  $R_5$ , and  $Z_6$  are as defined above. In a further embodiment of the present invention, the photoinitiator has the following structure:

G

$$X_{4} = \begin{pmatrix} R_{7} & Q & Z_{1} & Z_{2} \\ R_{6} & R_{1} & Q & N & R_{3} \end{pmatrix}$$

wherein  $X_4$ ,  $R_1$ ,  $R_2$ ,  $R_3$ ,  $R_4$ ,  $R_5$ ,  $R_6$ ,  $R_7$ ,  $Z_6$ , and  $Z_6$  are as defined above. Other photoinitiators of the present invention have the following structure:

$$X_4$$
 $R_5$ 
 $R_7$ 
 $R_5$ 
 $R_7$ 
 $R_7$ 
 $R_7$ 
 $R_7$ 
 $R_7$ 
 $R_7$ 
 $R_7$ 
 $R_7$ 
 $R_7$ 

PCT/US99/22590

23

wherein  $X_4$ ,  $R_1$ ,  $R_2$ ,  $R_3$ ,  $R_4$ ,  $R_5$ ,  $R_6$ ,  $R_7$ ,  $Z_9$ , and  $Z_6$  are as defined above.

In yet a further embodiment, the photoinitiator of the present invention has the following structure:

S

$$\begin{array}{c|c}
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & & & \\
 & &$$

wherein  $Z_6$  and  $Z_6$  are as defined above. In a further embodiment of the present invention, the photoinitiator of the present invention has the following structure:

5

The above-described photoinitiators of the present invention may be produced by the following reaction mechanism:

15

WO 00/18750

PCT/US99/22590

24

$$\begin{pmatrix}
\text{electron} \\
\text{domaing}
\end{pmatrix} > \times - C \\
R_1 \\
R_2$$

$$\begin{pmatrix}
x \\
x_4 \\
x_4 \\
x_4 \\
x_5 \\
x_6
\end{pmatrix} = X - C \\
X - R_4 \\
X - R_5$$

$$\begin{pmatrix}
x \\
x_4 \\
x_5 \\
x_6
\end{pmatrix} = X - C \\
X - R_4 \\
X - R_5$$

wherein a first compound reacts with a metal or nonmetal salt, Z<sub>4</sub>Z<sub>5</sub>Z<sub>6</sub>, to produce a photoinitiator of the present invention, having a five-member ring containing a metal or nonmetal atom, at least one nitrogen atom, two carbon atoms, and possibly an oxygen atom.

S

The present invention is further directed to novel photoinitiators having the following general structure:

10

$$\begin{array}{c} x_1 = C \\ x_2 = C \\ x_3 = C \\ x_4 = C \end{array}$$

wherein Y<sub>2</sub> and Y<sub>3</sub> each independently represent -O- or -N(R<sub>3</sub>)(R<sub>4</sub>)-; and X<sub>1</sub>, R<sub>1</sub>, R<sub>2</sub>, R<sub>3</sub>, R<sub>4</sub>, Z<sub>4</sub>, Z<sub>5</sub>, and Z<sub>6</sub> are as defined above. In one embodiment of the present invention, Y<sub>3</sub> represents -N(R<sub>3</sub>)(R<sub>4</sub>)- and Z<sub>6</sub> and Z<sub>6</sub> form two five member rings: one five member ring which includes Z<sub>4</sub>, Z<sub>5</sub>, and Z<sub>6</sub>, and one five member rings which includes with Z<sub>4</sub>, Z<sub>6</sub> and one of R<sub>3</sub> or R<sub>4</sub>. The resulting photoinitiator has the following structure:

5

PCT/US99/22590

23

wherein  $\mathbb{Z}_{r}$ ,  $\mathbb{Z}_{t}$  and  $\mathbb{R}_{t}$  comprise any combination of carbon, nitrogen and oxygen atoms to form two five member rings. It should be noted that  $\mathbb{Z}_{t}$ ,  $\mathbb{Z}_{t}$  and  $\mathbb{R}_{t}$  may form two similar ring structures or two different ring structures. Also, each ring formed by  $\mathbb{Z}_{t}$ ,  $\mathbb{Z}_{t}$  and  $\mathbb{R}_{t}$  may contain more than five ring members. In one embodiment of the present invention, the resulting photoinitiator has the following structure:

G

10

$$X_1 = C$$

$$X_1$$

wherein  $X_1$ ,  $Y_2$ ,  $R_1$ ,  $R_2$ ,  $R_3$ , and  $Z_4$  are as defined above; and  $n_1$  and  $n_2$  each independently represent an integer from 1 to 5. Desirably, the resulting photoinitiator has the following structure:

15

WO 00/18750

PCT/US99/22590

26

wherein  $R_1$ ,  $R_2$ ,  $R_3$ ,  $R_6$ ,  $R_7$ ,  $n_1$ , and  $n_2$  are as defined above.

In a further embodiment of the process investigation.

5

In a further embodiment of the present invention, Z<sub>8</sub> and Z<sub>8</sub> form a single ring. The resulting photoinitiator has the following structure:

$$\mathbf{x}_1 = \mathbf{c}$$

$$\mathbf{x}_2 = \mathbf{c}$$

$$\mathbf{x}_3$$

wherein Z<sub>6</sub> and Z<sub>6</sub> comprise any combination of carbon, nitrogen and oxygen atoms to form a ring. In one embodiment of the present invention, Z<sub>5</sub> and Z<sub>6</sub> form a five member ring so that the resulting photoinitiator has a dimeric structure. One example of the resulting photoinitiator has the following structure:

10

PCT/US99/22590

28

$$\mathbb{R} = \mathbb{R}$$

$$\mathbb{R}$$

Çī

wherein  $X_1$ ,  $Y_2$ ,  $Y_3$ ,  $Z_4$ ,  $R_1$  and  $R_2$  are as defined above. Other photoinitiators of the present invention having the above-described structure include, but are not limited to, the following photoinitiators:

5

and

and

10

15

wherein  $X_1$ ,  $Z_4$ ,  $R_1$  and  $R_2$  are as defined above. Other desirable photoinitiators include, but are not limited to, the following photoinitiators:

$$\begin{array}{c|c} R_1 & R_1 & R_2 \\ \hline R_6 & R_1 & R_6 \\ \hline R_6 & R_1 & R_6 \\ \hline \end{array}$$

wherein Z<sub>4</sub>, R<sub>1</sub>, R<sub>2</sub>, R<sub>3</sub>, R<sub>4</sub>, R<sub>6</sub> and R<sub>7</sub> are as defined above. Desirably, Z<sub>4</sub> comprises boron or zinc in the dimeric

29

structures for the photoinitiators of the present invention. structures above. It should be understood that the above photoinitiators of the present invention. used to form suitable dimeric structures Any combination of "X1", "Z", "Y", and "R" groups may be dimeric structures are only examples of suitable dimeric for

G

30%). extinction coefficient greater than about 25,000 l mole-1cm<sup>-1</sup> of the present invention have a high intensity of absorption. appropriate wavelength, the photoinitiators efficiently photoinitiators of the present invention have a molar than about 20,000 I mole-1cm-1. As a further example, the have a molar extinction coefficient (absorptivity) greater For example, the photoinitiators of the present invention produce one or more reactive species. The photoinitiators room humidity (from about 5% to 60%; desirably from 5% to room temperature (from about 15°C to 25°C) and normal The resulting photoinitiators are relatively stable a However, upon exposure to radiation at an

15

10

# Method of Generating a Reactive Species and Applications

20

of photochemical events per photon absorbed. a measure of the probability that a particular molecule a reactive species involves generating a reactive species by of generating a reactive species. The method of generating quantum yields may vary from zero (no absorption) to 1. photochemical process. More particularly, quantum yield is photochemical process. As stated above, the term "quantum photoinitiators to a radiation source triggers a exposing interaction with a photon. The term expresses the number yield" is used herein to indicate the efficiency of a photoinitiators to (photoinitiator) will absorb a quantum of light during its The present invention is further directed to a method one or more of the radiation. The exposure of the above-described

8

25

႘

WO 00/18750

PCT/US99/22590

မ

quantum yield being about 1.0. will be greater than about 0.99, with the most desirable quantum yield of the photoinitiators of the present invention will be greater than about 0.95. Still more desirably, the quantum yield of the photoinitiators of the present invention will be greater than about 0.9. Even more desirably, the quantum yield of the photoinitiators of the present invention a quantum yield greater than about 0.8. More desirably, the greater than that experienced with photoinitiators of the efficiency with which a reactive species is generated with which generates one or more reactive species. The photoinitiators of the present invention desirably will have prior art as indicated by faster cure times. For example, the the photoinitiators of the present invention is significantly molecule absorbs enough energy to cause a bond breakage, portions of the molecule. The excitable portion of the transfers the absorbed energy to one or more excitable photons having a relatively specific wavelength and The photoinitiators of the present invention absorb

10

G

synergists, and such other additives as are well known to materials as desired, such as pigments, extenders, amine the polymerization and curing media also may contain other known to one having ordinary skill in the art. In addition, curing of an unsaturated oligomer/monomer mixture. in any situation where reactive species are required, such as to radiation results in the generation of one or more those having ordinary skill in the art. unsaturated monomers and oligomers may be any of those for the polymerization of an unsaturated monomer and the reactive species. Thus, the photoinitiators may be employed Exposing the photoinitiators of the present invention

23

20

15

acrylic acid, monomers and oligomers include ethylene, propylene, vinyl By way of illustration only, examples of unsaturated isobutylene, styrene, methacylic acid, ethyl acrylate, isoprene, acrylonitrile,

35

31

methacrylate, vinyl acrylate, allyl methacrylate, tripropylene glycol diacrylate, trimethylol propane ethoxylate acrylate, epoxy acrylates, such as the reaction product of a bisphenol A epoxide with acrylic acid; polyether acrylates, such as the reaction product of acrylic acid with an adipic acid/ hexanediol-based polyether, urethane acrylates, such as the reaction product of hydroxypropyl acrylate with diphenylmethane-4,4'-diisocyanate, and polybutadiene diacrylate oligomer.

G

The types of reactions that various reactive species enter into include, but are not limited to, addition reactions, including polymerization reactions; abstraction reactions; rearrangement reactions; elimination reactions, including decarboxylation reactions; oxidation-reduction (redox) reactions; substitution reactions; and conjugation/deconjugation reactions.

15

10

polymerizable material, the intensity and wavelength of the curing is accomplished. It is to be understood that the mixture is employed in place of an unsaturated monomer, radiation, and the duration of exposure to the radiation photoinitiators, the identity and amount the art, and depends upon the identity and amount of material is readily determinable by one of ordinary skill in The amount of radiation sufficient to polymerize the amount of radiation sufficient to polymerize the material. the art, and that the mixture will be irradiated with an the present invention is to be admixed by means known in polymerizable material admixed with the photoinitiators of described above. When an unsaturated oligomer/monomer the effacious photoinitiators of the present invention the polymerizable material to radiation in the presence of an unsaturated monomer or epoxy compound, by exposing method of polymerizing a polymerizable material, such as Accordingly, the present invention also comprehends a

25

20

ဗ

WO 00/18750

PCT/US99/22590

32

In one embodiment of the present invention, one or more photoinitiators of the present invention are used to polymerize an epoxy resin. It is believed that the following reaction mechanism takes place in the presence of a hydrogen-donating compound, such as an alcohol, cumene or amine:

G

$$X = C \xrightarrow{N - R_1} \xrightarrow{\text{light}} Z_1 \text{ and/or } Z_2 \xrightarrow{H^+} HZ_1 \text{ and/or } HZ_2$$

$$R_1 \xrightarrow{R_2} R_3$$

Reactive species, HZ, and/or HZ, then react with an epoxy resin according to the following mechanism to produce a polyether:

The weak conjugate bases,  $Z_1^-$  and/or  $Z_2^-$ , which are non-nucleophilic, enable the polymerization reaction to take place, unlike other anions, which may prematurely terminate the polymerization reaction.

ഗ

Polymer Films, Coated Fibers and Webs, and Adhesive Compositions

10

the art, and depends upon the identity and amount of material is readily determinable by one of ordinary skill in The amount of radiation sufficient to polymerize the admixture into a film may be used in the present invention the same. Any method known in the art of drawing the coated nonwoven web or fiber, and a method for producing nonwoven web or on a fiber, thereby providing a polymerradiation. The admixture may be drawn into a film on a the thickness of the admixture formed, so long as accomplished. Any film thickness may be produced, as per unsaturated composition. with an amount of radiation sufficient to polymerize the the present invention, into a film and irradiating the film method for producing a film, by drawing an admixture of a admixture sufficiently polymerizes upon exposure to polymerizable material and one or more photoinitiators of The present invention further includes a film and a oligomer/monomer mixture, When the polymerizable material is an curing

20

15

25

35

WO 00/18750 PCT/US99/22590

<u>ω</u>

photoinitiator, the identity and amount of the polymerizable

material, the thickness of the admixture, the intensity and wavelength of the radiation, and duration of exposure to the radiation.

The present invention also includes an adhesive

S

irradiated to cure the composition. Similarly, the present invention includes a laminated with one or more photoinitiators of the present invention. unsaturated oligomer/monomer mixture, the adhesive is the unsaturated polymerizable material in the adhesive is an irradiated to polymerize the adhesive composition. above-described adhesive composition between the layers is wherein a structure having at least two layers with the invention provides a method of laminating a structure polyolefin nonwoven web or film. Accordingly, the present produced wherein at least one layer is a cellulosic or embodiment of the present invention, a laminate is with the above-described adhesive composition. In one structure comprising at least two layers bonded together composition comprising a polymerizable material admixed The present invention also includes an adhesive When

15

10

at least one of the layers allows sufficient radiation to to the radiation. wavelength of the radiation, and the duration of exposure identity and thickness of the layer, the intensity and polymerizable material, the thickness of the admixture, the amount of photoinitiator, the identity and amount of the ordinary skill in the art, and depends upon the identity and polymerize the admixture is readily determinable by one of pass through. Again, the amount of radiation sufficient to used as one of the layers so long as they allow radiation to polyolefin nonwoven web or film known in the art may be polymerize sufficiently. penetrate through the layer to enable the admixture to the laminates of the present invention, on the condition that It is to be understood that any layers may be used in Accordingly, any cellulosic or

8

25

35

discharge excimer lamp or radiation from a mercury lamp. nanometers. The radiation desirably will be incoherent, a wavelength of from about 4 to about 400 nanometers. pulsed ultraviolet radiation from a dielectric barrier desirably will have a wavelength of from 320 to about 420 from about 100 to about 420 nanometers, and even more More desirably, the radiation will have a wavelength of Desirably, the radiation will be ultraviolet radiation having about 900 nanometers. More desirably, the radiation will visible radiation; and near infrared radiation. Desirably, near ultraviolet and far or vacuum ultraviolet radiation; wavelength of from about 4 to about 1,000 nanometers present invention may be exposed generally will have a have a wavelength of from about 100 to 700 nanometers. the radiation will have a wavelength of from about 100 to Thus, the radiation may be ultraviolet radiation, including The radiation to which the photoinitiators of the

10

S

Excimers are unstable excited-state molecular complexes which occur only under extreme conditions, such as those temporarily existing in special types of gas discharge. Typical examples are the molecular bonds between two rare gaseous atoms or between a rare gas atom and a halogen atom. Excimer complexes dissociate within less than a microsecond and, while they are dissociating, release their binding energy in the form of ultraviolet radiation. The dielectric barrier excimers in general emit in the range of from about 125 nm to about 500 nm, depending upon the excimer gas mixture.

25

8

15

Dielectric barrier discharge excimer lamps (also referred to hereinafter as "excimer lamp") are described, for example, by U. Kogelschatz, "Silent discharges for the generation of ultraviolet and vacuum ultraviolet excimer radiation." Pure & Appl. Chem., 62, No. 9, pp. 16671674 (1990); and E. Eliasson and U. Kogelschatz, "UV Excimer Radiation from Dielectric- Barrier Discharges." Appl. Phys.

မွ

35

36
B. 46, pp. 299-303 (1988). Excimer lamps were developed by

ABB Infocom Ltd., Lenzburg, Switzerland, and at the present time are available from Heraeus Noblelight GmbH, Kleinostheim, Germany.

The excimer lamp emits incoherent, pulsed ultraviolet

Ç

radiation. Such radiation has a relatively narrow bandwidth, i.e., the half width is of the order of approximately 5 to 100 nanometers. Desirably, the radiation will have a half width of the order of approximately 5 to 50 nanometers, and more desirably will have a half width of the order of 5 to 25 nanometers. Most desirably, the half width will be of the order of approximately 5 to 15 nanometers.

5

The ultraviolet radiation emitted from an excimer lamp can be emitted in a plurality of wavelengths, wherein one or more of the wavelengths within the band are emitted at a maximum intensity. Accordingly, a plot of the wavelengths in the band against the intensity for each wavelength in the band produces a bell curve. The "half width" of the range of ultraviolet radiation emitted by an excimer lamp is defined as the width of the bell curve at 50% of the maximum height of the bell curve.

8

15

The emitted radiation of an excimer lamp is incoherent and pulsed, the frequency of the pulses being dependent upon the frequency of the alternating current power supply which typically is in the range of from about 20 to about 300 kHz. An excimer lamp typically is identified or referred to by the wavelength at which the maximum intensity of the radiation occurs, which convention is followed throughout this specification and the claims. Thus, in comparison with most other commercially useful sources of ultraviolet radiation which typically emit over the entire ultraviolet spectrum and even into the visible region, excimer lamp radiation is essentially monochromatic.

ၶ

37

photoinitiators of the present invention. may be manufactured for use with one or more specific addition, specialty lamps having a specific emission band another suitable lamp for use in the present invention. In nm. One lamp, the V-bulb available from Fusion Systems, is invention which have an absorption maximum at about 420 420 nm, may be used with photoinitiators of the present Other specialty doped lamps, which emit radiation at about corresponding to the emission peak of the mercury lamp. an absorption maximum of about 360 nanometers, one or more photoinitiators of the present invention having radiation source is particularly useful when matched with radicals from the above-described photoinitiators. emission peak of about 360 nm is used to produce free In a further embodiment of the present invention, a mercury radiation source known to those of ordinary skill in the art. photoinitiators of the present invention may be any the present invention, the source of radiation used with the technology provides the following potential advantages: lamp with a D-bulb, which produces radiation having an New lamp This

10

G

- substantially single wavelength output;
- unique wavelength output;

23

20

5

- ලලලම high intensity; and
- absence of radiation trapping

about 390 nanometers, some of the photoinitiators of the present invention will generate one or more reactive species the presence of a special light source. for the generation of reactive species that does not require photoinitiators of the present invention provides a method invention absorbing radiation in the range of about 250 to As a result of the photoinitiators of the present exposure ð sunlight. Accordingly, these

ၶ

ၾ

Although excimer lamps are highly desirable for use in

10

WO 00/18750

such light sources are necessary without the photoinitiators maintaining light sources in numerous industries wherein cure upon exposure to sunlight. These photoinitiators also of the present invention. photoinitiator is designed, the photoinitiator of the present exposure to sunlight. Therefore, depending upon how the polymerizable materials may be polymerized merely upon consumers can apply to a desired object and polymerize or production of adhesive and coating compositions that invention can eliminate the cost of purchasing and The photoinitiators of the present invention enable the industry applications wherein

G

of the present invention. However, the effectiveness of the of approximately 360 nm or 420 nm with the photoinitiators emission source, that emits radiation having a wavelength wavelength band radiation source. dependent upon the availability or use of a narrow photoinitiators of the present invention is not necessarily be desirable to utilize an excimer lamp, or other radiation band emitter, such as an excimer lamp. For example, it may much lower than, for example, radiation from a narrow band, even though the intensity of such radiation may be radiating source corresponding to the "tuned" wavelength utilize the target radiation in the emission spectrum of the photoinitiators of the present invention to more efficiently present invention for a specific wavelength band permits the The effective tuning of the photoinitiators of the

20

15

Composition Use of the Above-Described Photoinitiators IJ. an Ink

8

23

photoinitiators are incorporated into an ink jet ink embodiment of the present invention, one or more of the invention may be incorporated into ink compositions. In one composition for use on ink jet ink printers. The above-described photoinitiators of the present

39

the ink composition. one of the above-described radiation sources is used to cure may be used to cure the ink jet ink composition. Desirably, radiation source known to those of ordinary skill in the art instantaneous curing of the ink jet ink composition. source in series with the ink jet printing machine for printing machines alone or in combination with a radiation composition may be used on commercially available ink jet Aŋy

G

Use of the Above-Described Photoinitiators in Radiation-Drying Printing Process Other

10

which utilizes radiation as a drying means. printing, and flat-bed printing. operations, such as on a Heidelberg press, flexographic drying printing includes, for example, off-set printing on a radiation-drying printing press. As discussed above, more of the photoinitiators into an ink composition for use the present invention involves the incorporation of one or "radiation-drying printing" refers to any printing method A further use of the above-described photoinitiators of Radiation-

15

cold lamp as the light source. present invention, complete curing at an output rate of and a low energy light source. In one embodiment of the obtained while using a minimal amount of photoinitiator 10,000 printed sheets per hour may be obtained using a 50 W photoinitiators. Further, the increased output may be increased press output due to the photoreactivity of the The photoinitiators of the present invention enable

23

8

amount of photoinitiator added to the composition is from about 0.25 to about 3.0 wt% of the total weight of the the total weight of the composition. More desirably, the adhesive composition or resin is less than about 4.0 wt% of used in the printing processes disclosed herein. Desirably, the amount of photoinitiator added to the ink composition, Any of the above-described photoinitiators may be

30

ၾ

WO 00/18750 PCT/US99/22590

40

wt% of the total weight of the composition. A major advantage of the photoinitiators of the

added to the composition is from about 0.25 to about 2.0

composition. Most desirably, the amount of photoinitiator

G

printed sheet output is greater than 8,000 sheets per hour. greater than 6,000 sheets per hour. More desirably, the for photocuring, using a Heidelberg print press and a 50 W excimer cold lamp unobtainable. For example, in an open air printing process print speeds, which were at one time thought to be adhesive compositions or resins for printing presses enables photoinitiators of the present invention in ink compositions, present invention possess rapid curing times from 5-10 times Ink compositions containing the photoinitiators of the comparison to the curing times of prior art photoinitiators. ink compositions, adhesive compositions and/or resins in present invention is that they enable rapid curing times of 10,000 sheets per hour. Most desirably, the printed sheet output is greater than faster than the curing times of ink compositions containing best known photoinitiators. The use of desirably the printed sheet output is the

15

10

scope of the present invention. In the examples, all parts to be construed as limiting in any way either the spirit or the examples which follow. Such examples, however, are not are by weight, unless stated otherwise. The present invention is further described by the

25

20

COMPARATIVE EXAMPLE 1

Photocuring of CGI 369 in Red Flexo Resin

ဗ

in the form of a powder was added to a 1 g sample of red UV radiation while positioned within an FTIR machine to flexo ink (Gamma Graphics). The mixture was exposed to A mixture of Ciba Geigy photoinitiator 369 (CGI 369)

41

monitor the decrease in carbon-carbon double bonds within the mixture. The curing rate was measured.

#### **EXAMPLE 1**

Photocuring of One of KC's New Photoinitiators in Red Flexo Resin

S

A mixture of Kimberly Clark's photoinitiator, having the following structure, in the form of a powder was added to a 1 g sample of red flexo ink (Gamma Graphics).

5

The mixture was exposed to UV radiation while positioned within an FIIR machine to monitor the decrease in carboncarbon double bonds within the mixture. The curing rate was measured. The photoinitiator had a curing rate relative to the CGI 369 photoinitiator of greater than 220%.

15

#### **EXAMPLE 2**

Method of Forming a 1-(p-fluorophenyl)-2-dimethylamineethanone Intermediate to a Photoinitiator of the Present Invention

20

The following reaction was carried out as detailed elow:

$$F - \left( \bigcirc \right) - \stackrel{\square}{C} - CH_2Br + N \stackrel{CH_3}{CH_3} \xrightarrow{Ether} F - \left( \bigcirc \right) \stackrel{\square}{C} CH_2N \stackrel{CH_3}{CH_3}$$

$$CH_3 \xrightarrow{CCH_2N} CH_3$$

WO 00/18750

PCT/US99/22590

42

Into a three-necked round-bottom flask was placed 200 ml of anhydrous diethyl ether with stirrer bar and bubbler inlet. The ether was cooled to 0°C. Dimethyl amine was bubbled into the solvent for 1 hour to make a saturated solution. Into the flask was placed 10.0 g (0.046 mole) of 1-p-fluorophenacyl bromide dissolved in 50 ml of ether over a period of about 20 minutes. The temperature of the mixture was kept at 0°C for about 4 hours and then allowed to raise to room temperature overnight. The reaction mixture was then filtered to remove the dimethyl amine hydroxide and the solvent to yield a yellow oil. The oil was pumped in a vacuum oven and used in further examples without further purification. The final product was 1-(p-fluorophenyl)-2-dimethylamine-ethanone and the yield of the reaction was 7.5 g of oil (94%).

5

G

#### **EXAMPLE 3**

15

Method of Forming a 1-(p-fluorophenyl)-2-dimethylamine-2-methyl-propanone Intermediate to a Photoinitiator of the Present Invention.

20

The following reaction was carried out as detailed below:

$$\left\langle \bigcirc \right\rangle \stackrel{\text{CH}_3}{\text{CCH}_3} \stackrel{\text{CH}_3}{\text{CH}_3} + \text{CH}_3 \text{I} + \text{NaOH} \xrightarrow{\text{CH}_3\text{CN}} F - \left\langle \bigcirc \right\rangle \stackrel{\text{CH}_3}{\text{CH}_3} \stackrel{\text{CH}_3}{\text{CH}_3} \stackrel{\text{CH}_3}{\text{CH}_3}$$

Into a 1-liter, round-bottom flask was placed 5.0 g (0.028 mole) of the 1-(p-fluorophenyl)-2-dimethylamine-ethanone compound of Example 1, 8.6 g (0.062 mole) of methyl iodide, and 330 ml of acetonitrile. The reaction mixture was stirred for about 4 hours. The solvent was then removed and replaced with 300 ml of water and 7.3 g of a 34 wt% solution of sodium hydroxide (0.07 mole). The reaction mixture was then heated at about 55°C to 60°C for about 1 hour. On cooling, the reaction mixture was extracted with

30

PCT/US99/22590

ť

ether, and dried over magnesium sulfate. The solvent was removed under reduced pressure to yield an oil which was pumped in the vacuum oven. The product crystallized in a refrigerator overnight. The final product was measured to be 4.1 g of 1-(p-fluorophenyl)-2-dimethylamine-2-methyl-propanone and the yield was found to be about 71%.

S

#### **EXAMPLE 4**

Method of Forming a Piperazine-Containing Intermediate to a Photoinitiator of the Present Invention

G

10

The following reaction was carried out as detailed below:

Into a 250 ml, round-bottom flask was placed 1.4 g (0.01 mole) of potassium carbonate, 2.0 g of the product from Example 2, 0.86 g (0.01 mole) of piperazine, and 20 ml of N,N-dimethylformamide (DMF). The mixture was flushed with argon for about 20 minutes prior to heating at reflux. The reaction mixture was heated at reflux for about 16 hours. HPLC indicated a 80% conversion to the desired product shown below (This was the only compound having a 325 nm UV absorption peak.) The crude product was recrystallized from ethanol to yield a pale yellow solid. The yield of the reaction was 1.8 g of 1-piperazine-2-dimethylamine-2-methyl-propanone (69%).

20

15

#### **EXAMPLE 5**

25

23

Method of Forming a Zn-Containing Photoinitiator of the Present Invention

The following reaction was carried out as detailed below:

ဗ

WO 00/18750

PCT/US99/22590

4

$$\bigcap_{CH_{3}}\bigcap_{C$$

In order to form one of the photoinitiators of the present invention, zinc chloride containing water was heated under an argon gas atmosphere to produce zinc chloride free of water. Into a 250 ml, three-necked, round-bottom flask fitted with condenser, argon gas inlet, and bubbler outlet was placed 2.6 g ( 0.019 mole) of ZnCl<sub>2</sub>. The flask was continuously flushed with argon while the ZnCl<sub>2</sub> was heated with a propane torch. The ZnCl<sub>2</sub> was heated for about 15 minutes until it melted. Heating was continued for about ten minutes and then the ZnCl<sub>2</sub> was allowed to cool under an argon atmosphere. The product was ground to form a powder, still under an argon atmosphere.

10

The resulting ZnCl<sub>3</sub>, 80 ml of benzene, and 8 g of the 1-morpholino-2-dimethylamine-2-methyl-propanone produced in Example 4 were heated at reflux for about 12 hours in an argon atmosphere. The solution was then cooled and filtered. The solvent was removed under reduced pressure to yield a yellow powder. The powder was pumped in a vacuum oven at ambient temperature to yield 6.9 g of photoinitiator (yield 79%) having the structure above.

20

15

Samples of the yellow solid were mixed into offset black resins (GERBER-SCHMIDT GmbH, Frankfurt, Germany) at 2.0 wt% based on the total weight of the resin. The resins were drawn down into a thin film and exposed to an excimer lamp (308 nm). The resins fully cured after 1-2 flashes (0.05 seconds/flash). The control prepared with

PCT/US99/22590

45

IRGACURE® 369 (available from Ciba Geigy) took 6-8 flashes and was still not fully cured.

#### **EXAMPLE 6**

Method of Forming a New Zn-Containing Photoinitiator

G

In order to form one of the photoinitiators of the present invention, zinc chloride containing water was heated under an argon gas atmosphere to produce zinc chloride free of water. Into a 1-liter, three-necked flask was placed 7.4 g (0.05 mole) of ZnCl<sub>2</sub>. The flask was continuously flushed with argon while the ZnCl<sub>3</sub> was heated with a propane torch. The ZnCl<sub>2</sub> was heated until it liquified. Heating was continued for about ten minutes and then the ZnCl<sub>3</sub> was allowed to cool. The product was ground to form a powder, still under an argon atmosphere.

10

The resulting ZnCl<sub>y</sub>, 200 ml of benzene, and 20 g (0.05 mole) of IRGACURE® 369 (available from Ciba Geigy) having the following structure

15

were heated at reflux for about 12 hours in an argon atmosphere. The solution was then cooled and filtered. The solvent was removed under reduced pressure.

8

The resulting modified-369 compound had the following structure:

23

PCT/US99/22590

WO 00/18750

46

The yellow solid was found to have a similar retention time and UV absorption compared to IRGACURE® 369. However, the cure rate of a resin containing the yellow solid was 3 to 5 times faster than the cure rate of an identical resin containing the IRGACURE® 369 photoinitiator.

Samples of the yellow solid were mixed into effect and

10

G

Samples of the yellow solid were mixed into offset and flexo resins (GERBER-SCHMIDT GmbH, Frankfurt, Germany) at 2.0 and 3.0 wt% based on the total weight of the resin. The resins were printed onto white plates and exposed to an excimer lamp (308 nm) or a mercury lamp (360 nm). The resins rapidly cured.

15

#### **EXAMPLE 7**

Method of Forming a New BF3-Containing Photoinitiator

20

Into a 1-liter, three-necked flask was placed 100 g (0.275 mole) of IRGACURE® 369 and 500 ml of dry benzene. The flask was continuously flushed with argon and cooled in an ice bath. Into the flask was added 38.8 g (0.0275 mole) of boron trifluoride etherate. The reaction was carried out in the dark and stirred at 0°C for about 10 hours.

A yellow precipitate formed and was filtered. The solvent was removed under reduced pressure to yield 82.1 g (69% yield) of a yellow solid.

47

HPLC indicated a different retention time and a UV absorption at about 415 nm.

Samples of the yellow solid were mixed into offset and flexo resins at 2.0 and 3.0 wt% based on the total weight of the resin. The resins were rapidly cured when printed onto white plates and exposed to a Fusion Systems 'V' Bulb (420 nm).

G

#### **EXAMPLE 8**

Method of Forming a New BCl<sub>3</sub>-Containing Photoinitiator

5

Into a 1-liter, three-necked flask was placed 10 g (0.027 mole) of IRGACURE® 369 and 50 ml of dry benzenc. The flask was continuously flushed with argon and cooled in an ice bath. Into the flask was added 3.16 g (0.027 mole) of boron trichloride in xylene. The reaction was stirred overnight at 0°C for about 10 hours.

15

A yellow precipitate formed and was filtered. The solvent was removed under reduced pressure to yield 11.2 g (86% yield) of a yellow solid.

HPLC indicated a retention time and a UV absorption similar to IRGACURE® 369.

20

Samples of the yellow solid were mixed into offset resins at 2.0 wt% based on the total weight of the resin. The resins were rapidly cured when drawn down onto white plates and exposed to an excimer lamp (308 rm).

 $\aleph$ 

#### **EXAMPLE 9**

Offset Printing Using Photoinitiators of the Present

Invention

ဗ

Two lots of Zn-containing photoinitiator were prepared as in Examples 2-5 above. The lots were designated Z1029 and Z106. Offset printing trials were performed at the Institute for Surface Modification (Leipzig, Germany) using Gerber Schmidt highly pigmented black ink compositions.

႘ၟ

WO 00/18750 PCT/US99/72590

48

The photoinitiator was added to the ink composition and mixed using a high speed vortex mixer. After mixing for about 15 minutes, the temperature was measured to be about 60°C. Similar ink compositions were prepared using IRGACURE® 369.

Ç

A sheet-fed offset press manufactured by Heidelberg Press, Model No. GT052, was used to print sheets using the above ink compositions. The press ran up to 8,000 sheets per hour. The curing took place in a nitrogen atmosphere or in air. The results of the printing test are given below in Table 1.

5

Table 1. Cure Results of Offset Printing

90% cured.	U.5 Wt% PI 369
Good surface cure. Soft under the surface.	1.0 wt% Z1029 and
	0.5 wt% PI 369
Hard solid cure. 100% cured.	1.0 wt% Z1029 and
	0.5 wt% PI 369 ***
Good surface cure. 95% cured.	1.0 wt% Z1029 and
	0.5 wt% PI 369
Hard surface cure. 100% cured.	1.0 wt% Z1029 and
	0.25 wt% PI 369 ***
Good surface cure. 95% cured.	1.0 wt% Z1029 and
	0.25 wt% PI 369
Good surface cure. 95% cured.	1.0 wt% Z1029 and
	0.25 wt% PI 369
Good surface cure, but soft under the	0.75 wt% Z1029 and
Resin was better than the PI 369. 90% cured.	1.0 wt% Z1029
Resin was even better. 85% cured.	2.0 wt% Z1029
Resin was better, but still soft. 80% cured.	3.0 wt% Z1029
Resin was poor. 70 to 80% cured.	4.0 wt% Z1029
Resin was very poor, even wet.	1.0 wt% PI 369
Resin was soft, poorly cured.	4.0 wt% PI 369 ***
Resin was soft. 95% cured.	4.0 wt% PI 369
Observations	Photoinitiator
0	

PCT/US99/22590

49

	1.0 wt% Z1029 and	Hard solid cure. 100% cured.
_	0.75 wt% PI 369	
_	1.0 wt% Z1029 and	Good surface cure. Good cure under the
	0.75 wt% PI 369 ***	surface. 98% cured.
	1.0 wt% Z1029 and	Hard solid cure. 100% cured.
	1.0 wt% PI 369	
	1.0 wt% Z1029 and	Good surface cure. Good cure under the
	1.0 wt% PI 369 ***	surface, 96% cured

\*\*\* Test was run in air, as opposed to a nitrogen atmosphere.

As shown in Table 1, photoinitiator systems of the present invention consistently provided better cure than IRGACURE® 369 alone. The photoinitiators of the present invention provided good cure results in a nitrogen atmosphere, as well as, in air.

G

### **EXAMPLE 10**

70

Method of Forming a New Cationic Photoinitiator

In order to form one of the photoinitiators of the present invention, zinc tetrafluoroborate (available from Aldrich) was heated overnight at 50°C in a vacuum oven (0.01 mm Hg) to produce zinc tetrafluoroborate free of water. The dried solid and ether were mixed to form a 0.5M solution of zinc tetrafluoroborate in ether.

15

Four grams (0.01 mole) of IRGACURE® 369 (available from Ciba Geigy) having the following structure

20

23

WO 00/18750

50

PCT/US99/22590

was dissolved in 100 ml of ether (anhydrous) in a three-necked round bottom flask fitted with stirrer bar, argon gas bubbler, and condenser. To this solution was added, via a syringe, 21.5 ml of the 0.5M Zn(BF<sub>4</sub>), ether solution over 10 minutes. The clear solution turned cloudy. A white precipitate formed over a period of an hour. The white precipitate was filtered on a Buckner funnel and washed with 100 ml of anhydrous ether. The powder was then pumped in a vacuum for over an hour at room temperature.

5

The resulting compound had the following structure:

10

#### **EXAMPLE 11**

Curing Process Using a Cationic Photoinitiator

15

In a beaker 8.5 g of CYRACURE® UVR-6110 (cycloaliphatic diepoxide, available from Union Carbide) was heated to 50°C while stirring with a magnetic stirrer. Into the beaker was added 0.1 g of the photoinitiator produced from Example 1, which was allowed to dissolved over a period of 2 minutes. Into the beaker, 2.5 g of UCAR-VAGH (vinyl chloride-vinyl acetate-vinyl alcohol terpolymer, available from Union Carbide) was slowly added while stirring resulting in a clear solution after about 3 minutes.

51

A drop of the mixture was drawn down onto a metal plate. The film was exposed to a medium pressure mercury arc lamp. The film immediately went from being tacky to fully cured.

#### **EXAMPLE 12**

G

Method of Forming a 1-(2,6-dimethoxy-4-fluorophenyl)-2-methylpropan-1-one Intermediate to a Photoinitiator of the Present Invention

The following reaction was carried out as detailed below:

5

$$F - CCH_3$$
 $+ (CH_3)_2CHCOCI$ 
 $AlCl_3$ 
 $F - CCH_3$ 
 $CCH_3$ 
 $CCH_3$ 
 $CCH_3$ 
 $CCH_3$ 

Into a 1-liter, three-necked round-bottom flask was placed 20.0 g (0.13 mole) of 1,3-dimethoxy-5-fluorobenzene, 13.6 g (0.0.13 mole) of 2-methylpropanoyl chloride, and 100 ml of nitrobenzene. The mixture was flushed with argon and an equal molar amount of AlCl<sub>3</sub> (17.2 g) was added to the reaction mixture while stirring at 5°C. The mixture was stirred at a temperature of 5°C for about 1 hour after the addition of the AlCl<sub>3</sub>. The reaction mixture was then mixed with about 100 ml of distilled water and extracted with dichloromethane. The organic layer was washed with NaHCO<sub>3</sub> solution, salt water, and then dried. The solvent was removed by vacuum to yield the final product, 1-(2,6-dimethoxy-4-fluorophenyl)-2-methylpropan-1-one. The yield of the reaction was 22.8 g of product (77%).

8

15

30

25

WO 00/18750 PCT/US99/12590

52

#### **EXAMPLE 13**

Method of Forming a Morpholino-Containing Intermediate to a Photoinitiator of the Present Invention

The following reaction was carried out as detailed below:

Ú

Into a 1-liter, three-necked round-bottom flask was placed 15.0 g (0.07 mole) of 1-(2,6-dimethoxy-4-fluorophenyl)-2-methylpropan-1-one produced in Example 12,5.8 g (0.07 mole) of morpholine, and 19.0 g (0.14 mole) of K<sub>2</sub>CO<sub>3</sub> in 100 ml. of dimethylsulfoxide (DMSO). The mixture was flushed with argon and heated to reflux overnight. The reaction mixture was cooled and then mixed with about 100 ml of distilled water and extracted with dichloromethane. The organic layer was washed with NaHCO<sub>3</sub> solution, salt water, and then dried. The solvent was removed by vacuum to yield the final product, 1-(2,6-dimethoxy-4-morpholinophenyl)-2-methylpropan-1-one. The yield of the reaction was 18.1 g of product (88%).

5

ಕ

#### **EXAMPLE 14**

Method of Forming a Morpholino-Containing Bromide
Salt Intermediate to a Photoinitiator of the Present
Invention

25

20

The following reaction was carried out as detailed below:

မ

53

$$\begin{array}{c} \text{OCH}_{\text{J}} \\ \text{OCH}_{\text{J}} \\ \text{CC} \xrightarrow{\text{CH}_{\text{J}}} + \text{HBr} \\ \text{CH}_{\text{J}} \\ \text{COH}_{\text{J}} \\ \end{array} \begin{array}{c} \text{OCH}_{\text{J}} \\ \text{OCH}_{\text{J}} \\ \text{CH}_{\text{J}} \\ \text{COH}_{\text{J}} \\ \end{array}$$

Into a 1-liter, three-necked round-bottom flask was placed 15.0 g (0.05 mole) of 1-(2,6-dimethoxy-4-morpholinophenyl)-2-methylpropan-1-one produced in Example 13 and 150 ml. of glacial acetic acid. Hydrogen bromide gas was bubbled through the mixture for about 40 minutes. The product was then used in the next step, disclosed in Example 15.

#### **EXAMPLE 15**

Method of Forming a Morpholino-Containing Bromide-Containing Salt Intermediate to a Photoinitiator of the Present Invention

15

10

5

The following reaction was carried out as detailed below:

Into a 1-liter, three-necked round-bottom flask was placed 19.1 g (0.05 mole) of the product produced in Example 14. The mixture was chilled to 5°C. To the chilled mixture was added dropwise 8.0 g of Br, over a period of about one hour. The mixture was then stirred for about one hour. The solvent was removed under vacuum to yield a pale

20

20

WO 00/18750 PCT/US99/72590

2

yellow/orange solid. The yield of the final product was 20.9 g of product (92%).

**EXAMPLE 16** 

Method of Forming a Morpholino-Containing Bromide-Containing Salt Intermediate to a Photoinitiator of the Present Invention

G

The following reaction was carried out as detailed below:

10

Br OCH<sub>3</sub> CH<sub>3</sub>

R<sub>2</sub> CC(-Br + H<sub>2</sub>N(CH<sub>2</sub>)<sub>2</sub>NH(CH<sub>2</sub>)<sub>2</sub>NH<sub>2</sub>CH<sub>2</sub>

K<sub>2</sub>CO<sub>3</sub> toluene

K<sub>2</sub>CO<sub>3</sub> toluene

CH<sub>2</sub> -CH<sub>3</sub>

OCH<sub>3</sub> CH<sub>2</sub> -CH<sub>3</sub>

OCH<sub>3</sub> CH<sub>3</sub> CH<sub>2</sub>-CH<sub>3</sub>

NH

OCH<sub>3</sub> CH<sub>3</sub> CH<sub>3</sub> CH<sub>3</sub>-CH<sub>3</sub>

NH

OCH<sub>3</sub> CH<sub>3</sub> CH<sub>3</sub>-CH<sub>3</sub>

NH

Into a 1-liter, three-necked round-bottom flask was placed 15.0 g (0.03 mole) of the product produced in Example 17,3.1 g (0.03 mole) of diethylenetriamine, 8.2 g (0.06 mole) of K<sub>2</sub>CO<sub>3</sub>, and 100 ml. of toluene. The mixture was heated at reflux overnight. The solvent was removed under vacuum to yield a yellow solid. The yield of the final product was 8.7 g of product (74%).

55

**EXAMPLE 17** 

Method of Forming a Zn-complex Photoinitiator of the Present Invention

below: The following reaction was carried out as detailed

G

yield a yellow solid. The yield of the final product was 5.4 g materials were stored for about one hour at room 0.6M solution of Zn(OEt<sub>2</sub>) <sub>2</sub>Cl<sub>2</sub> in ether). of product (96%). 1.72 g (0.013 mole) of Zn(OEt<sub>2</sub>) <sub>2</sub>Cl<sub>2</sub> in ether (i.e., 21 ml. of a placed 5.0 g (0.013 mole) of the product produced in Example temperature. The solvent was removed under vacuum to 18 and 50 ml. of toluene. To the mixture was slowly added Into a 1-liter, three-necked round-bottom flask was The reaction

5

ដ

WO 00/18750

PCT/US99/22590

56

**EXAMPLE 18** 

Testing of Zn-Containing Photoinitiator of the Present Invention in a Red Flexographic Resin

excimer lamp (308 nm). The resin fully cured after 4 flashes A sample containing 0.1 g of the photoinitiator produced in Example 19 and 1.0 g of a red flexographic down on a white panel. The thin film was exposed to a 50W (0.01 seconds/flash). resin was prepared. Adrop of the resin sample was drawn

G

embodiments. Accordingly, the scope of the present alterations to, variations of, and equivalents to these appreciated that those skilled in the art, upon attaining an understanding of the foregoing, may readily conceive of and any equivalents thereto. invention should be assessed as that of the appended claims with respect to specific embodiments thereof, it will be While the specification has been described in detail

15

10

PCT/US99/22590

57

Claims

What is claimed is:

A photoinitiator having the following formula:

5

wherein X<sub>1</sub> comprises a conjugated system of one or more aryl groups or substituted aryl groups; Z<sub>1</sub> comprises -O, -S, an alkyl group having from one to six carbon atoms, an ester moiety, a ketone moiety, an amine moiety, an imine moiety, an ether moiety, an aryl or substituted aryl group, a metal or non-metal, or a metal or non-metal containing group; and M<sub>1</sub> comprises an alkyl group, a substituted alkyl group, or forms a five-member ring with Z<sub>1</sub>.

10

2. The photoinitiator of Claim 1, wherein  $X_1$  comprises

15

$$\begin{array}{c} \begin{array}{c} \begin{array}{c} \\ \\ \\ \\ \\ \\ \end{array} \end{array}$$

20

WO 00/18750 PCT/US99/12590

58

wherein R<sub>6</sub> and R<sub>7</sub> each independently represent hydrogen, an alkyl group having from one to six carbon atoms, an alkoxy group having from one to six carbon atoms, or a halogen-substituted alkyl group; and wherein y<sub>1</sub> and y<sub>2</sub> each independently represent a hydrogen, an alkyl group having from one to six carbon atoms, an aryl group,

G

10

wherein  $X_3$  represents a hydrogen, an alkyl or substituted alkyl group, or an aryl or substituted aryl group.

59

comprises a tertiary alkyl group having the following The photoinitiator of Claim 1, wherein M1

σı

hydrogen, an alkyl group having from one to six carbon atoms, a tertiary amine group, an aryl group, or a substituted aryl group. wherein y3, y4 and y5 each independently represent a

5

 $Z_1$  form a five-member ring. The photoinitiator of Claim 1, wherein M1 and

15

photoinitiator has the following structure: The photoinitiator of Claim 5, wherein the

group, or an aryl or substituted aryl group; and  $R_1$  and  $R_2$  are each independently a hydrogen atom, an alkyl or independently a hydrogen atom, an alkyl or substituted alkyl bond with the oxygen atom; R, R3 and R4 are each metal containing salt, or -C(O)R, which forms a covalent wherein  $Z_2$  is a metal or non-metal atom, a metal or non-

20

13

20

WO 00/18750

PCT/US99/22590

8

PCT/US99/22590

or form one or more aromatic rings with  $X_1$ . substituted alkyl group, or an aryl or substituted aryl group,

and  $X_1$  form a photoinitiator having the structure below: The photoinitiator of Claim 6, wherein R1, R2,

G

atoms, an aryl group, hydrogen, an alkyl group having from one to six carbon wherein y11 and y12 are each independently represent a

70

alkyl group, or an aryl or substituted aryl group. wherein X3 represents a hydrogen, an alkyl or substituted

15

The photoinitiator of Claim 6, wherein the

photoinitiator comprises

PCT/US99/22590

కు

61

ç

20

9

5

ç

15

$$X_1 = C$$

$$R_1 \longrightarrow R_2$$

$$R_2 \longrightarrow R_3$$

G,

The photoinitiator of Claim 5, wherein the photoinitiator has the following structure:

wherein Y is -O- or  $-N(R_5)-$ ;  $Z_3$  is a metal or nonmetal cation or a salt containing the cation;  $R_3$  and  $R_4$  are each independently a hydrogen atom, an alkyl or substituted alkyl group, or an aryl or substituted aryl group; and  $R_1$  and  $R_2$  are each independently a hydrogen atom, an alkyl or substituted alkyl group, or an aryl or substituted aryl group, or form one or more aromatic rings with  $X_1$ .

ස

10. The photoinitiator of Claim 5, wherein the photoinitiator has the following structure:

$$X_1 = C$$

$$X_2 = C$$

$$X_2 = C$$

$$X_2 = C$$

$$X_3 = C$$

$$X_4 = C$$

$$X_2 = C$$

$$X_2 = C$$

$$X_3 = C$$

$$X_4 = C$$

$$X_4 = C$$

$$X_5 = C$$

$$X_5 = C$$

$$X_7 = C$$

$$X_7$$

wherein  $Y_2$  and  $Y_3$  each independently represent -O- or  $-N(R_3)(R_4)-; R_3$ , and  $R_4$  are each independently a hydrogen atom, an alkyl or substituted alkyl group, or an aryl or substituted aryl group;  $R_1$  and  $R_2$  are each independently a hydrogen atom, an alkyl or substituted alkyl group, or an aryl or substituted aryl group or form one or more aromatic rings with  $X_1; Z_4$  is a metal or nonmetal atom; and  $Z_5$  and  $Z_6$  are halogen-containing anions or form one or more rings with or without  $R_3$  or  $R_4$ .

5

G

11. The photoinitiator of Claim 10, wherein Z<sub>4</sub> comprises Cd, Hg, Zn, Mg, Al, Ga, In, Tl, Sc, Ge, Pb, Si, Ti, Sn, Zr, boron or phosphorus.

5

12. The photoinitiator of Claim 10, wherein  $Z_5$  and  $Z_6$  each independently comprise fluorine, chlorine or bromine-containing anions.

20

 $\aleph$ 

WO 00/18750

PCT/US99/12590

13. The photoinitiator of Claim 10, wherein the photoinitiator comprises

2

wherein  $R_6$  and  $R_7$  each independently represent hydrogen, an alkyl group having from one to six carbon atoms, an alkoxy group having from one to six carbon atoms, or a halogen-substituted alkyl group.

G

14. The photoinitiator of Claim 10, wherein the photoinitiator has the following structure:

10

$$X_4$$
 $R_5$ 
 $R_1$ 
 $R_5$ 
 $R_1$ 
 $R_5$ 
 $R_1$ 
 $R_5$ 
 $R_5$ 

wherein X<sub>4</sub> comprises any nitrogen-containing group, which donates a pair of electrons to the nitrogen-carbon double bond; and R<sub>5</sub> and R<sub>7</sub> each independently represent hydrogen, an alkyl group having from one to six carbon atoms, an alkoxy group having from one to six carbon atoms, or a halogen-substituted alkyl group.

15

65

15. The photoinitiator of Claim 9, wherein the photoinitiator has the following structure:

$$\begin{array}{c|c} X_1 & & & \\ & & & \\ X_6 & R_1 & & \\ & & & \\ R_6 & R_1 & & \\ & & & \\ R_2 & R_3 & \\ & & & \\ \end{array}$$

atoms, an alkoxy group having from one to six carbon atoms, or a halogen-substituted alkyl group. wherein  $X_4$  comprises any nitrogen-containing group, which donates a pair of electrons to the nitrogen-carbon double hydrogen, an alkyl group having from one to six carbon bond; and R<sub>6</sub> and R<sub>7</sub> each independently represent

10

photoinitiator has the following structure: The photoinitiator of Claim 10, wherein the

15

$$X_1 = \underbrace{\begin{array}{c} R_7 \\ R_6 \\ R_1 \\ R_2 \end{array}} \underbrace{\begin{array}{c} Z_1 \\ Z_2 \\ R_3 \\ R_3 \end{array}} \underbrace{\begin{array}{c} Z_1 \\ Z_2 \\ Z_3 \\ Z_4 \\ Z_5 \\ Z_7 \\ Z_8 \\ Z_9 \\$$

$$X_4 = \begin{pmatrix} R_7 & R_5 \\ R_6 & R_1 & R_2 \end{pmatrix} \times \begin{pmatrix} R_7 & R_7 \\ R_7 & R_7 \end{pmatrix}$$

WO 00/18750

PCT/US99/22590

8

$$\begin{array}{c|c}
 & \xrightarrow{R_7} & \xrightarrow{C_2} & \xrightarrow{C_2} & \xrightarrow{C_2} & \xrightarrow{C_2} & \xrightarrow{C_1} &$$

ç

5

comprising: 17. A method of generating a reactive species,

irradiating the cationic photoinitiator of Claim 1 with radiation.

10

A method of polymerizing a polymerizable

material, comprising:

irradiating an admixture of a polymerizable material and the photoinitiator of Claim 1.